

Robuuste en gekende topkwaliteit - 55 jaar ervaring -
Innovatief - service van op afstand



Technische kenmerken :

- Tankinhoud : 37 Lt
- Tankweerstand : 4,5 kW
- Pompvermogen : 2,0 kW - 2,7 Pk
- Boilerinhoud : 12 Lt
- Boilerweerstand : 5,4 kW
- Totaal vermogen : 7,4 kW - 16 Amp
- Voltage : 400 V 3N+ T - 50 Hz
- Aquatech doseer en naspoelpomp : 370 W
- Waterconsumptie per cycli : 2,0 Lt
- Aangeraden watertoevoer : +55° C- 2 Bar
- Waterhardheid : 7+10° f
- Aantal korven/ u : 30 st
- Gewicht : 150 kg
- Afmetingen : 775 B x 810 D x 1360 H mm/
1440 H mm bij geopende deur

Standaard meegeleverd :

- 1 x RVS mand 600 B x 670 D x 100 H mm
- 1 x RVS plateninzet 5 compartimenten
- 1 x Bestekmand

Vaat & pannen & pottenwasser EL951 E Met korfafmeting 600 x 670 mm Incl. breaktank & naspoeldrukverhogingspomp & ingebouwde afvoerpomp

Productvoordelen :

- **UNIKO FULL WIFI DISPLAY**
- Service & foutdiagnose via **IKLOUD**
- 1 zeer krachtige spoelpomp van 2000 Watt
- Geschikt voor GN 1/1 schalen (530 x 325 mm)
- **Geschikt voor Euronorm bakken—E/2 kisten (400 x 600 mm)**
- Maximale pothoogte : 445 mm
- Compleet uitgerust en volautomatische elektronische sturing met digitale aanduiding & controlesysteem = Energie- en wasmiddelbesparing
- Dot Matrix Touch display uit gehard glas
- Automatische instelling van alle parameters tijdens de eerste installatie
- Nauwkeurige instelling van temperatuur en dosering
- **4 Standard-Spoelprogramma's: 120-150-240-540 sec.**
- **Andere Spoelprogramma's individueel programmeerbaar**
- Geruisloze werking en energie besparend dankzij de dubbelwandige deur
- Spoelpomp en breaktank voor een spoeling bij constante temperatuur en druk
- Dubbele thermo/acoustische wand
- Spoel- en wasarmen in RVS - Onderaan gescheiden
- Dubbel elektronisch verstelbare dispenser voor was- en glansspoelmiddel
- Micro veiligheidsschakelaar bij onvoorziën openen van de deur
- Veiligheidsthermostaat met handmatige reset
- Inclusief doseerpomp voor wasmiddel en glansmiddel
- Alle belangrijke componenten vanaf de voorkant toegankelijk
- Onderhouds- en reinigingswerkzaamheden eenvoudig uit te voeren
- Hydraulische soft deur opening & sluiting
- **Zelfreinigingsprogramma—automatisch ledigen boiler**

MET ACQUATECH-SYSTEEM VOOR GEGARANDEERDE HYGIENE

- Verandering van schoon water (totaal of gedeeltelijk) bij elke wasbeurt - Wastank met ingebouwde RVS filter

Interesse? Bezoek onze showroom (na afspraak) of vraag ons om vrijblijvend advies.

Frank Schepens
+32 475 76.96.05
info@allfoodmachines.be



Showroom

Gereneerde merken

Vakbekwame service

Afspraak = Afspraak

Gemakkelijk bereikbaar

Luc Delhaye
+32 499 923 933
luc@allfoodmachines.be

All Food Machines bv

Begoniastraat 23D Industriezone B- 9810 Eke Tel: 09/ 384.04.74 - www.allfoodmachines.be



ELITECH LINE EL951E

TYPE	Warewasher
LINE	ELITECH LINE
BASKET	600x670
SIZE	775x810x1360h

Thanks to its dimensions, the **EL951E** model can be used **both as large dishwasher and as warewasher**. In fact, its basket can wash 26 dishes per cycle, GN1/1 gastronorm trays, baking trays and 600x400 dough trays and objects measuring up to 575x645x445(h)mm with a maximum productivity of 30 baskets/hour (780 dishes/hour). The practical work height facilitates loading while the double walls improve thermal-acoustic insulation. The **rounded moulded tank with integral filters** ensures maximum hygiene and perfect draining.

The dishwashers of the **ELITECH** line ensure maximum performance thanks to the standard Acquatech System which, through an atmospheric boiler and rinse pump, maintains **constant temperature and pressure** and optimum water consumption. Elitech ensures a sanitising rinse cycle and proves to be the perfect choice for canteens, nursing homes, pastry shops, bakers and butchers where compliance with HACCP rules is essential. For anyone seeking perfectly sparkling glasses, it is possible to connect a **Reverse Osmosis System** which purifies water and reduces detergent and rinse-aid consumption, ensuring excellent results and perfect glasses without the need for hand drying. The innovative **UNIKO tempered glass touch screen display** makes any operation simple and intuitive, from the choice of the most suitable wash cycle to its progress control, as well as constantly monitor the status of the dishwasher with ease. The large variety of wash cycles makes the dishwasher customisable according to your needs. Constant self-diagnosis allows you to minimise machine downtime, promptly warning the technician through the **Wi-Fi IKLOUD** control system that offers the possibility of remotely changing the dishwasher parameters and resolving the situation in real-time.

The electronic control allows you to manage various parameters to give you an absolute customisation level and the continuous **self-diagnosis** allows you to **minimise machine downtime**, suggesting some operations that need to be verified. The **self-cleaning cycle** at the end of the day cleans the wash tank and empties the hot water from the boiler, preventing limestone from building up inside. The standard **double peristaltic electric rinse-aid and detergent dispenser** ensures the best result from each wash cycle with great savings thanks to the precise dosage managed by the electronic card; whereas, the **moulded washing and rinsing arms** ensure great reliability and durability. The **Thermo-stop** function checks that washing and rinsing begin only when the desired temperature is reached. The bodywork is made entirely of **AISI 304 s**

