

Robuuste en gekende topkwaliteit - 55 jaar ervaring -
Innovatief - service van op afstand



Technische kenmerken :

- Tankinhoud : 100 Lt
- Tankweerstand : 9,0 kW
- Pompvermogen : 2 x 2,0 kW - 2 x 2,7 Pk
- Boilerinhoud : 20,8 Lt
- Boilerweerstand : 9,0 kW
- Totaal vermogen : 13,0 kW - 32 Amp
- Voltage : 400 V 3N+ T - 50 Hz
- Aquatech doseer en naspoelpomp: 2 x 370 W
- Waterconsumptie per cycli : 4,0 Lt
- Aangeraden watertoevoer : +55° C- 2 Bar
- Waterhardheid : 7+10° f
- Aantal korven/ u : 60 st
- Gewicht : 340 kg
- Afmetingen : 1445 B x 860 D x 1980 H mm/
2300 H mm bij geopende deur

Standaard meegeleverd :

- 2 x RVS mand 600 B x 670 D x 100 H mm
- 2 x RVS plateninzet 5 compartimenten
- 2 x Bestekmand

Vaat & pannen & pottenwasser EL991 E Met korfafmeting 2 x 600 x 670 mm Incl. breaktank & naspoeldrukverhogingspomp & ingebouwde afvoer pomp

Productvoordelen :

- **UNIKO FULL WIFI DISPLAY**
- Service & foutdiagnose via **IKLOUD**
- **2 zeer krachtige spoelpompen van elk 2000 Watt**
- Geschikt voor GN 1/1 schalen (530 x 325 mm)
- **Geschikt voor Euronorm bakken - E/2 kisten (3 x 400 x 600 mm naast elkaar)**
- Geschikt voor GN 2/1 schalen (530 x 650 mm)
- Geschikt voor bakplaten (600 x 800 mm)
- Maximale pothoogte : 840 mm
- Compleet uitgerust en volautomatische elektronische sturing met digitale aanduiding & controlesysteem = Energie- en wasmiddelbesparing
- Dot Matrix Touch display uit gehard glas
- Automatische instelling van alle parameters tijdens de eerste installatie
- Nauwkeurige instelling van temperatuur en dosering
- **4 Standaard-Spoelprogramma's: 120-150-240-540 sec**
- **Andere Spoelprogramma's individueel programmeerbaar**
- Geruisloze werking en energie besparend dankzij de dubbelwandige deur
- Spoelpomp en breaktank voor een spoeling bij constante temperatuur en druk
- Dubbele thermo/acoustische wand
- Spoel- en wasarmen in RVS - Onderaan gescheiden
- **Zelfreinigingsprogramma - automatisch ledigen boiler**
- Dubbel elektronisch verstelbare dispenser voor was- en glansspoelmiddel
- Micro veiligheidsschakelaar bij onvoorzien openen van de deur
- Veiligheidsthermostaat met handmatige reset
- Inclusief doseerpomp voor wasmiddel en glansmiddel
- Alle belangrijke componenten vanaf de voorkant toegankelijk
- Onderhouds- en reinigingswerkzaamheden eenvoudig uit te voeren
- Hydraulische soft deursluiting
- **MET ACQUATECH-SYSTEEM VOOR GEGARANDEERDE HYGIENE**
- Verandering van schoon water (totaal of gedeeltelijk) bij elke wasbeurt - Wastank met ingebouwde RVS filter

Interesse? Bezoek onze showroom (na afspraak) of vraag ons om vrijblijvend advies.

Frank Schepens
+32 475 76.96.05
info@allfoodmachines.be



Showroom

Gereneerde merken

Valkbekwame service

Afspraak = Afspraak

Gemakkelijk bereikbaar

Luc Delhaye
+32 499 923 933
luc@allfoodmachines.be

All Food Machines bv

Begoniastraat 23D Industriezone B- 9810 Eke Tel: 09/ 384.04.74 - www.allfoodmachines.be



ELITECH LINE EL991E

TYPE	Warewasher
LINE	ELITECH LINE
BASKET	600x670
SIZE	1445x855x2015/2290h

The **EL991E** warewasher is the answer for anyone who has to effectively wash objects measuring up to 575x645x825(h)mm inside its **two baskets**, thanks to the **two wash pumps** and two rinse pumps. It is suitable for washing baking trays, pots of various kinds, mixing bowls, utensils and even 52 dishes at each cycle as it is equipped with two baskets with a maximum productivity of 60 baskets/hour (3120 dishes/hour). The work height and the **counterbalanced door** facilitate loading while the **double walls** improve thermal-acoustic insulation. The **rounded moulded tank with integral filters** ensures maximum hygiene and perfect draining.

The dishwashers of the **ELITECH** line ensure maximum performance thanks to the standard Acquatech System which, through an atmospheric boiler and rinse pump, maintains **constant temperature and pressure** and optimum water consumption. Elitech ensures a sanitising rinse cycle and proves to be the perfect choice for canteens, nursing homes, pastry shops, bakers and butchers where compliance with HACCP rules is essential. For anyone seeking perfectly sparkling glasses, it is possible to connect a **Reverse Osmosis System** which purifies water and reduces detergent and rinse-aid consumption, ensuring excellent results and perfect glasses without the need for hand drying. The innovative **UNIKO tempered glass touch screen display** makes any operation simple and intuitive, from the choice of the most suitable wash cycle to its progress control, as well as constantly monitor the status of the dishwasher with ease. The large variety of wash cycles makes the dishwasher customisable according to your needs. Constant self-diagnosis allows you to minimise machine downtime, promptly warning the technician through the **Wi-Fi IKLOUD** control system that offers the possibility of remotely changing the dishwasher parameters and resolving the situation in real-time.

The electronic control allows you to manage various parameters to give you an absolute customisation level and the continuous **self-diagnosis** allows you to **minimise machine downtime**, suggesting some operations that need to be verified. The **self-cleaning cycle** at the end of the day cleans the wash tank and empties the hot water from the boiler, preventing limestone from building up inside. The standard **double peristaltic electric rinse-aid and detergent dispenser** ensures the best result from each wash cycle with great savings thanks to the precise dosage managed by the electronic card; whereas, the **moulded washing and rinsing arms** ensure great reliability and durability. The **Thermo-stop** function checks that washing and rinsing begin only when the desired temperature is reached. The bodywork is made entirely of **AISI 304 steel** and has been designed with all of the components in the front for **easy technical assistance**. Sturdy and reliable dishwashers to best deal with every moment of your day.

DISHWASHERS FEATURES	ELITECH LINE EL991E
Dimensions - (mm) L - P - H	1445x855x2015/2290h
n° baskets/hour - (+55°C)	Max 60
Height pot max	830mm
LT bread basket	2 x 100
Trays	GN1/1 - 60x40 GN2/1 - 60x80
Tank heating element - Tank capacity	9,0 kW - 100lt
Boiler heating element - Boiler capacity	9,0kW - 20,8lt
Washing pump	2 x 2,0kW / 2 x 2,7Hp
Total power input / Current	13,0kW / 32A
Standard input voltage	400V3N+T 50Hz
Recommended inlet water temperature	+55°C
Water hardness	7÷10 °f
Water consumption per cycle (inlet suggested pressure 2 BAR)	4,0-5,0lt
Adjustable detergent and rinse-aid dispenser	ELECTRIC
Acquatech system rinse	si
ACCESSORI	
8 division cutlery insert	2
Integral tank filter	1 + 1
Inox basket dim.600x670x100mm	2
Basket for trays with 5 compartments	2
OPTION	
UNIKO touch display with IKLOUD Wi-Fi control	●
Booster pump kit 0,5Hp	-
Drain pump kit 40W	●
Boiler heating element 4,5kW	●
Boiler heating element 5,4kW	●
Reverse osmosis system	-
Kit 4 Stainless steel feet 50-70mm	-

● Optional Installabile, - Optional not installabile

EL991E

