

Robuuste en gekende topkwaliteit - 55 jaar ervaring -
Innovatief - service van op afstand



Technische kenmerken :

- Tankinhoud : 37 Lt
- Tankweerstand : 4,5 kW
- Pompvermogen : 1,34 kW- 1,8 Pk
- Boilerinhoud : 7,3 Lt
- Boilerweerstand : 5,4 kW
- Totaal vermogen : 6,74 kW - 16 Amp
- Voltage : 400 V 3N+ T - 50 Hz
- Aquatech doseer en naspoelpomp : 250 W
- Waterconsumptie per cycli : 2,0 Lt
- Aangeraden watertoevoer : +55° C- 2 Bar
- Waterhardheid : 7+10° f
- Aantal korven/ u : 60 st
- Gewicht : 133 kg
- Afmetingen : 620 B x 770 D x 1435 H mm/
1900 H mm bij geopende deur

Standaard meegeleverd :

- 1 x RVS mand 600 B x 670 D x 100 H mm
- 1 x RVS plateninzet 5 compartimenten
- 2 x Tankfilter
- 1 x Bestekmand voor plateau's

Doorschuif pannen & pottenwasser Type EL60 E

Met korfmeting 500 x 500 mm
Incl. breaktank & naspoeldrukverhogingspomp
& ingebouwde afvoerpomp

Productvoordelen :

- **UNIKO FULL WIFI DISPLAY**
 - Service & foutdiagnose via **IKLOUD**
 - 1 zeer krachtige spoelpomp van 1340 Watt - 1,8 pk
 - Geschikt voor GN 1/1 schalen (530 x 325 mm)
 - Maximale pothoogte : 390 mm
 - Compleet uitgerust en volautomatische elektronische sturing met digitale aanduiding & controlesysteem = Energie- en wasmiddelbesparing
 - Dot Matrix Touch display uit gehard glas
 - Automatische instelling van alle parameters tijdens de eerste installatie
 - Nauwkeurige instelling van temperatuur en dosering
 - **4 Standard-Spoelprogramma's: 60-90-120-300 sec.**
 - **Andere Spoelprogramma's individueel programmeerbaar**
 - Geruisloze werking en energie besparend dankzij de dubbelwandige deur
 - Spoelpomp en breaktank voor een spoeling bij constante temperatuur en druk
 - Dubbele thermo/acoustische wand
 - Spoel- en wasarmen in RVS - Onderaan gescheiden
 - **Zelfreinigingsprogramma—automatisch ledigen boiler**
 - Dubbele elektronisch verstelbare dispenser voor was- en glansspoelmiddel
 - Micro veiligheidsschakelaar bij onvoorzien openen van de deur
 - Veiligheidsthermostaat met handmatige reset
 - Inclusief doseerpomp voor wasmiddel en glansmiddel
 - Alle belangrijke componenten vanaf de voorkant toegankelijk
 - Onderhouds- en reinigingswerkzaamheden eenvoudig uit te voeren
 - Hydraulische soft deur opening & sluiting
 - **MET ACQUATECH-SYSTEEM VOOR GEGARANDEERDE HYGIENE**
 - Verandering van schoon water (totaal of gedeeltelijk) bij elke wasbeurt - Wastank met ingebouwde RVS filter
- Mogelijke optie :**
- Ingebouwde waterontharder = Type ELS 60 E

Interesse? Bezoek onze showroom (na afspraak) of vraag ons om vrijblijvend advies.

Frank Schepens
+32 475 76.96.05
info@allfoodmachines.be



Showroom



Gerenomeerde merken



Vakbekwame service



Afspraak = Afspraak



Gemakkelijk bereikbaar

All Food Machines bv

Begoniastraat 23D Industriezone B- 9810 Eke Tel: 09/ 384.04.74 - www.allfoodmachines.be



ELITECH LINE EL60E

TYPE	Pass-through dishwasher
LINE	ELITECH LINE
BASKET	500x500
SIZE	620x770x1435/1900h

The dishwashers of the ELITECH line ensure maximum performance thanks to the standard Acquatech System which, through an atmospheric boiler and rinse pump, maintains constant temperature and pressure and optimum water consumption. Elitech ensures a sanitising rinse cycle and proves to be the perfect choice for canteens, nursing homes, pastry shops, bakers and butchers where compliance with HACCP rules is essential. For those who seek glass perfection, it is possible to connect a Reverse Osmosis System which purifies water and reduces detergent and rinse-aid consumption, ensuring excellent results and perfect glasses without the need for hand drying.

The innovative UNIKO tempered glass touch screen display makes any operation simple and intuitive, from the choice of most suitable wash cycle to its progress control, as well as constantly monitor the dishwasher state with ease. The large variety of wash cycles makes the dishwasher customisable according to your needs. Constant self-diagnosis allows you to minimise machine downtime, promptly warning the technician thanks to the Wi-Fi IKLOUD control system that gives the possibility to act remotely to change the dishwasher parameters and resolve the situation in real-time.

The EL60E hood type dishwasher is the right solution for businesses that are faced with the washing of different types of dishes, proving capable of washing glasses, dishes, medium sized objects up to 500x500x390(h)mm and GN 1/1 baking trays in only 620 mm wide, ensuring a maximum productivity of 60 baskets/hour (1080 dishes/hour). The hood type models are fitted with an easily removable basket support for easy cleaning and a rounded moulded tank with integral filters for perfect draining and absolute hygiene. The "PUSH TO START" cycle start system ensures less waste preventing the start of empty washes. The Reverse Osmosis System, the suitable detergents and the tilted basket make the EL60E model excellent for treating your glasses gently.

The electronic control allows you to manage various parameters to give you an absolute customisation level and the continuous self-diagnosis allows you to minimise machine downtime, suggesting some operations to be verified. The self-cleaning cycle at the end of the day cleans the wash tank and empties the boiler from the hot water, preventing limestone forming inside. The standard double peristaltic electric rinse-aid and detergent dispenser ensures the best result from each wash cycle with great savings thanks to the precise dosage managed by the electronic card; whereas, the moulded washing and rinsing arms ensure great reliability and durability. The Thermo-stop function checks that washing and rinsing begin only when the desired temperature is reached. The bodywork is made entirely of AISI 304 steel and has been designed with all components in the front to allow easy technical assistance. Sturdy and reliable dishwashers to best deal with every moment of your day.

DISHWASHERS FEATURES	ELITECH LINE EL60E
Dimensions - (mm) L - P - H	620x770x1435/1900h
n° baskets/hour - (+55°C)	Max 60
Height glass max	390mm
Ø height plate max	415mm
Height pot max	390mm
LT bread basket	40 (H=390mm)
Trays	GN1/1
Tank heating element - Tank capacity	4,5kW - 37lt
Boiler heating element - Boiler capacity	5,4kW - 7,3lt
Washing pump	1,34Kw / 1,8 Hp
Total power input / Current	6,74 kW / 16A
Standard input voltage	400V3N+T / 230V 50Hz
Recommended inlet water temperature	+55°C
Water hardness	7÷10 °f
Water consumption per cycle (inlet suggested pressure 2 BAR)	2,0lt GUARANTEED
Adjustable detergent and rinse-aid dispenser	ELECTRIC
Acquatech system rinse	si
ACCESSORI	
Basket for glasses dim.500x500x100mm	1
Basket for 18 dishes dim.500x500x100mm	2
8 division cutlery insert	1
Integral tank filter	2
OPTION	
UNIKO touch display with IKLOUD Wi-Fi control	●
Input voltage 230V/3+T	●
Booster pump kit 0,5Hp	-
Drain pump kit 40W	●
Boiler heating element 9kW	●
Stainless steel tank filter kit for rack dishwasher 500x500	●
Reverse osmosis system	●
Modular basket for wine glasses 500mm	●
Basket for trays with 4 compartments dim.500x500x200mm	●
Inclined basket for wine glasses dim.500x500x170mm	●
Kit 4 Stainless steel feet 50-70mm	-
Remote control with LCD display	●
● Optional Installabile, - Optional not installabile	

EL60E

